

Sky Factory eScape™ 2.0 Digital Cinema

DC-eScape-4726 Specifications

Monitor:

55" (1397mm) Professional LED Edgelit LCD Monitor
Resolution: 1920 x 1080

Mounting Pan with Integrated Video-Audio Playback Equipment:

Mounting Pan

16 gauge steel, powder coated silver
Provides one location for all playback equipment
Protects eScape monitor and video-audio playback equipment, facilitates wiring, and provides ventilation for proper cooling
Rough opening: call The Sky Factory for specific requirements.
Requires wire access from top during rough-in for power, signal cable to controller, and audio cable

Video-audio playback equipment

Simple plug-in module for additional content

Wall Mounted Controller

Wired via Cat 6 cable

Simple illuminated push button operation

Fits in single gang outlet box

Low voltage mounting bracket provided

Keypad bezel available in white, almond or black

Standard Decora style faceplate available in white, almond, black or stainless steel

Other faceplate options available from Leviton

Speakers

Two 2-way speakers

5.25" (133mm) dia. woofer, 0.5" (13mm) tweeter

7.95" (202mm) dia. trim ring comes in white, can be painted

6.625" (168mm) dia. rough opening, 3.2" (80mm) mounting depth

Tile bridge and backcan enclosure for drop ceiling applications

Backcan is UL Listed for air handling spaces

2.26 lbs (1.03kg)

Cabling:

One plenum rated Cat 6 or better cable

Monitor location to wall mounted controller

Ends terminated with RJ45 connectors

35' (15.3m) standard, alternate lengths available if specified

Plenum rated speaker cable

monitor location to speaker locations

70' (30.6m) standard, or 35' (15.3m) +/- per speaker (alternate lengths available if specified)

Trim:

Wood or brushed anodized clear or black aluminum (style and material selected by client)

Sizes vary with style and material selection

33 9/16" (852mm) to 36 1/8" (918mm) wide

54 5/16" (1380mm) to 57 1/2" (1461mm) high

7/16" (11mm) to 2" (51mm) deep from wall surface

Electrical Requirements:

Total Power Consumption: 201 Watts Typ

Circuit Recommendations: a separate circuit is advisable

Power Surge Protection: recommended, but not provided

Operating Temperature: 32F ~ 94F (0C ~ 40C)

Operating Humidity: 10% ~ 80 % non-condensing

Fixture Weight:

98.8 lbs + 11.1 - 34.9 lbs depending on trim choice

(44.8kg + 5 - 15.8kg depending on trim choice)

Warranty:

2 year Sky Factory, Inc. limited warranty on entire system

eScape™

Recessed Wall Mount
High-Definition (HD)
Digital Cinema Virtual Window



Viewable Area:

approx. 47" x 26" (1193mm x 660mm)
depending on trim selection

Video Content (provided):

8, 12 or 16 hours of full HD Resolution (1920 x 1080) videos
Recorded in Ultra HD
Mastered and played back in high bit-rate Full HD
More footage capacity available in the future
Simple plug-in module for additional content

Notice: This product is NOT compatible with MRI and high energy particle imaging environments, such as Linac.

**This document specifies product only.
For rough opening and installation specifications,
call the Sky Factory.**